PATENT COOPERATION TREATY

From the INTERNATIONAL PRELIMINARY EXAMINING AUTHORITY

To:

ROSHARDT, Werner A.
KELLER & PARTNER PATENTANIMAETERAGEN
Schmiedenplatz 5

Postfach

CH-3000 Bern 7

SUISSE

19. Jan. 2005

Keller & Partner AG

PCT

NOTIFICATION OF TRANSMITTAL OF THE INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Rule 71.1)

IMPORTANT NOTIFICATION

Date of mailing

(day/month/year)

17.01.2005

Applicant's or agent's file reference

RS/hr-16149

International filing date (day/month/year) Priority date (

International application No. PCT/CH 03/00231

09.04.2003

Priority date (day/month/year)

01.10.2002

Applicant

DELTA ENERGY SYSTEMS (SWITZERLAND) AG et al.

- The applicant is hereby notified that this International Preliminary Examining Authority transmits herewith the international preliminary examination report and its annexes, if any, established on the international application.
- 2. A copy of the report and its annexes, if any, is being transmitted to the International Bureau for communication to all the elected Offices.
- 3. Where required by any of the elected Offices, the International Bureau will prepare an English translation of the report (but not of any annexes) and will transmit such translation to those Offices.

4. REMINDER

The applicant must enter the national phase before each elected Office by performing certain acts (filing translations and paying national fees) within 30 months from the priority date (or later in some Offices) (Article 39(1)) (see also the reminder sent by the International Bureau with Form PCT/IB/301).

agreement of the control of the cont

Where a translation of the international application must be furnished to an elected Office, that translation must contain a translation of any annexes to the international preliminary examination report. It is the applicant's responsibility to prepare and furnish such translation directly to each elected Office concerned.

For further details on the applicable time limits and requirements of the elected Offices, see Volume II of the PCT Applicant's Guide.

The applicant's attention is drawn to Article 33(5), which provides that the criteria of novelty, inventive step and industrial applicability described in Article 33(2) to (4) merely serve the purposes of international preliminary examination and that "any Contracting State may apply additional or different criteria for the purposes of deciding whether, in that State, the claimed inventions is patentable or not" (see also Article 27(5)). Such additional criteria may relate, for example, to exemptions from patentability, requirements for enabling disclosure, clarity and support for the claims.

Name and mailing address of the international preliminary examining authority:

<u>)</u>

European Patent Office D-80298 Munich Tel. +49 89 2399 - 0 Tx: 523656 epmu d Fax: +49 89 2399 - 4465 Authorized Officer

Fasbender, A

Tel. +49 89 2399-2380



PATENT COOPERATION TREATY PCT

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Article 36 and Rule 70)

Applicant's or agent's file reference RS/nr-16149				FOR FURTHER A	See Notification of Transmittal of International Preliminary Examination Report (Form PCT/IPEA/416)					
Interna PCT/			lication No. 0231	International filing date (day/month/year) 09.04.2003			Priority date (day/month/year) 01.10.2002			
Interna H01F			ent Classification (IPC) or b	l oth national classification	and IPC		·			
Applica DEL1		NEF	RGY SYSTEMS (SWIT	ZERLAND) AG et a	l.					
			national preliminary exar and is transmitted to the				rnational Preliminary Examining			
2.	This	REP	ORT consists of a total of	of 5 sheets, including t	his cover	sheet.				
	×	bee		pasis for this report and	d/or shee	s containing re	on, claims and/or drawings which have ectifications made before this Authority he PCT).			
	Thes	se an	nexes consist of a total o	of 5 sheets.						
3.	Thie	zono	rt contains indications re	lating to the following i	tome:	·	grand grand and a grand section of			
J.	iinə			latting to the lonowing i	lems.					
	1		Basis of the opinion							
]] []]		Priority	i-ion with rogard to r	savaltu in	···antiva atan a	ad indicate an alicability			
	 III ☐ Non-establishment of opinion with regard to novelty, inventive step and industrial applicability IV ☒ Lack of unity of invention 					па іпацькня аррікаріну				
	V	⊠	•	nder Rule 66.2(a)(ii) w		to novelty, inv	ventive step or industrial applicability;			
,	VI		Certain documents cite	ed						
,	VII		Certain defects in the i	nternational application	n					
,	VIII		Certain observations o	n the international app	lication					
Date o	f sub	missic	on of the demand	-	Date of	completion of thi	s report			
30.04	30.04.2004			17.01.	2005	•				
	Name and mailing address of the international preliminary examining authority:			Authoriz	ed Officer	the Potento				
prelimi		Eu: D-8 Tel	ining authority: ropean Patent Office 30298 Munich . +49 89 2399 - 0 Tx: 52365 c: +49 89 2399 - 4465	66 epmu d	Gols, C) ne No. +49 89 23	399-2616			

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No.

PCT/CH 03/00231

	D		
I.	Basis	or the	report

1. With regard to the **elements** of the international application (Replacement sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to this report since they do not contain amendments (Rules 70.16 and 70.17)):


	Description, Pages							
	1-2	0	as originally filed					
	Cla	ims, Numbers						
	1-2	0	received on 31.12.2004 with letter of 22.12.2004					
	Dra	wings, Sheets						
	1/4-	4/4	as originally filed					
2.	Wit lanç	h regard to the langu guage in which the in	lage, all the elements marked above were available or furnished to this Authority in the ternational application was filed, unless otherwise indicated under this item.					
	The	These elements were available or furnished to this Authority in the following language: , which is:						
		the language of a translation furnished for the purposes of the international search (under Rule 23.1(b)).						
		the language of publication of the international application (under Rule 48.3(b)).						
		Rule 55.2 and/or 55.	•					
3.	 With regard to any nucleotide and/or amino acid sequence disclosed in the international applicat international preliminary examination was carried out on the basis of the sequence listing: 							
		contained in the inte	rnational application in written form.					
	 ☐ filed together with the international application in computer readable form. ☐ furnished subsequently to this Authority in written form. 							
☐ furnished subsequently to this Authority in computer readable form.								
		The statement that the subsequently furnished written sequence listing does not go beyond the disclosure in the international application as filed has been furnished.						
		The statement that t listing has been furn	he information recorded in computer readable form is identical to the written sequence ished.					
4. The amendments have resulted in the cancellation of:								
		the description,	pages:					
		the claims,	Nos.:					
		the drawings,	sheets:					

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No.

PCT/CH 03/00231

									•
5.		This report has been estableen considered to go beyon					not been ma	de, since t	they have
		(Any replacement sheet correport.)	ntaining	such amen	dments must	be referred	d to under ite	m 1 and a	annexed to this
6.	Add	ditional observations, if neces	sary:	-					
IV	. Lac	ck of unity of invention		•					
1.	ln r	response to the invitation to re	estrict o	pay addition	onal fees, the	applicant h	nas:		
		restricted the claims.			•		· :		
		paid additional fees.							
		paid additional fees under p	rotest.	-					
		neither restricted nor paid a	dditiona	l fees.				•	
2.		This Authority found that the Rule 68.1, not to invite the a					nplied with a	nd chose,	according to
3.	This	s Authority considers that the	require	ment of uni	ty of invention	n in accorda	ance with Ru	les 13.1, 1	13.2 and 13.3
		complied with.							
		not complied with for the fol	lowing r	easons:				-	
4.		nsequently, the following part mination in establishing this		internationa	al application	were the su	ubject of inte	rnational p	preliminary
	\boxtimes	all parts.							
		the parts relating to claims I	los						
V.	Rea cita	asoned statement under Ar ations and explanations su	ticle 35(porting	(2) with req such stat	gard to novel ement	lty, inventiv	ve step or ir	ıdustrial <i>a</i>	applicability;
1.	Stat	tement							
	Nov	velty (N)	Yes: No:	Claims Claims	1-20				
	·lnve	entive step (IS)	Yes: No:	Claims Claims	1-20		,		
	Indu	ustrial applicability (IA)	Yes: No:	Claims Claims	1-20				•
2.	Cita	tions and explanations							
	see	separate sheet					•		



EXAMINATION REPORT - SEPARATE SHEET

1. Claim 1:

Technical field: A coil form for forming an inductive element with a core Prior art: X-documents DE-A-19 505 463 and EP-A-0 293 617 disclose a coil form according to the preamble of claim 1.

Problem: To provide a coil form allowing improved heat dissipation.

Solution: The coil form according to claim 1 is characterised in that separating plates are spaced at a specific plate-distance, where a ratio of the plate-distance to a diameter of the wire is between 1 and 2.

Inventive step: in the X-documents additional to the use of separating plates, insulating platers are added between the coils and separating plates. These insulating plates decrease the heat dissipation of the coils. The defined ratio for the plate-distance ensures that the wire winding wound in the coils area is in close contact with the separating plate made of metal, whereby the heat dissipation through the separating plate is improved. None of the available prior art suggests the above-mentioned ratio for the plate-distance. Consequently claim 1 meets the requirements of Articles 33(2) - (4) EPC.

2. Claim 18:

The claim relates to a method for forming an inductive element by positioning separating plates at a specific plate-distance by winding a wire in the coil area thereby pressing the separating plates against a side support. The pressing of the separating plates against the side support, causes the wound wire to be pressed against the separating plates. It is concluded that claim 18 meets the requirements of Articles 33(2) - (4) EPC for the reason as given above.

3. Claims 2 - 17 and 19 - 20:

The subject-matter of these claims relates to embodiments of the invention as set out in the independent claims and as such meet the requirements of Article 33(2) -(4) PCT.





PCT/CH 03/00231

EXAMINATION REPORT - SEPARATE SHEET

- 1. To meet the requirements of Rule 5.1(a)(ii) PCT, one of the documents DE-A-19 505 463 and EP-A-0 293 617 should have been identified in the description and the relevant background art disclosed therein should have been briefly discussed.
- 2. The description is not in conformity with the claims as required by Rule 5.1(a)(iii) PCT. Especially the embodiments relating to the deleted originally filed claims should have been removed from the application documents.

VII, VIII

1. In claim 18 it should have been made clear that "a separating plate (3)" relates to the "separating plates (103)" (Article 6 PCT).

10/530114 CH0300231

Application-No. 2004/032158
Applicant: Delta Energy Systems (Switzerland) AG,

JC13 R PCT/PTO 01 APR 2005

21

New claims 1 - 20

- 1. A coil form (1, 1.1) for forming an inductive element with a core (11.1, 11.2), including
- a) at least two coils,
- b) a hollow coil body (2) for insertion of the core, the coil body (2) being made of an electrically insulating material and
 - c) at least two separating plates (3, 3.1) which surround the outer surface of the coil body thereby providing at least one coil area (15, 15.1) on the outer surface of the coil body for holding a wire (16) that forms a part of a coil,
- 10 characterised in that
 - d) each separating plate is made of metal, includes an opening (4) for pushing the separating plate over the coil body and a slit (5) for prohibiting short circuits and leakage currents within the separating plate, and in that the separating plate forms a winding of another coil (16);
- e) the separating plates are spaced at a specific plate-distance,
 - f) where a ratio of the plate-distance to a diameter of the wire is between 1 and 2.
- A coil form according to claim 1, characterised in that the coil body (2) includes a coil portion (6) of a kind of a hollow cylinder for slipping over the separating plate (3) and a flange portion (7) on an end region of the coil portion.
 - 3. A coil form according to claim 2, characterised in that it includes two separating plates and in that the coil portion includes a second flange portion on a second end region of the coil portion, the flange portions forming a side support for the separating plates.

Application-No.: 2004/032158
Applicant: Delta Energy Systems (Switzerland) AG,



22

4. A coil form according to claim 3, characterised in that it includes four separating plates and a projection (123) that surrounds the outer surface of the coil body (102), the projection forming a side support for two separating plates.

5

- 5. A coil form according to claim 4, characterised in that a ratio of the plate-distance to a diameter of the wire is between 1.1 and 1.4.
- 6. A coil form according to any of claims 1 to 5, characterised in that the coil portion (106) includes a recess (127) on an inner surface and an opening (126) in its outer surface in a region of said recess, where said wire (128) is fed from an outside of the coil portion to an inside of the coil portion through said recess and from the inside of the coil portion to the outer surface of the coil portion through said opening.
- 7. A coil form according to any of claims 1 to 6, characterised in that said flange portion includes a plurality of holes, where a pin (125) is inserted into at least one hole, said pin being electrically conductively connectable to an end of one of the coils.
- 8. A coil form according to any of claims 1 to 7, characterised in that two or more separating plates are electrically conductively connected to form a plurality of windings of the second coil.
 - A coil form according to any of claims 1 to 8, characterised in that a shape of the opening (4) of the separating plate substantially corresponds to a shape of the outer

5

10

15

20

Application-No.: (CH2003/000231 Publication-No.: 2004/032158 Applicant: Delta Energy Systems (Switzerland) AG,



23

surface of the coil body and in that an internal diameter of the separating plate is smaller than an outer diameter of the coil body.

- 10. A coil form according to any of claims 1 to 9, characterised in that the coil body comprises at least two elements (20.1, 20.2) with means (21, 22) to fit the elements together to form the coil body.
- 11. A coil form according to claim 10, characterised in that the coil body comprises a first and a second element (20.1, 20.2) and in that the means to fit the elements together include a recess (21) on the first element and a corresponding projection (22) on the second element.
 - 12. A coil form according to any of claims 10 to 11, characterised in that the coil portion is of a kind of a right cylinder, where the coil body is separated into two elements by a plane being perpendicular to a base plane of the right cylindrical coil portion.
 - 13. A coil form according to claim 2, characterised in that the coil portion includes a recess (8) for positioning of the separating plate and in that the flange portion includes a plurality of terminals (9) where at least one terminal is electrically conductively connectable to an end of one of the at least two coils.
 - 14. A coil form according to any of claims 1 to 13, characterised in that a single separating plate is replaced by a plate group (130) where each plate group includes two separating plates and an insulation plate (119) between the separating plates.

5

10

15

20

Application-No.: 2004/032158 Applicant: Delta Energy Systems (Switzerland) AG,



24

- 15. An inductive element with a coil form according to any of claims 1 to 14, including a core (11.1, 11.2) inserted into the hollow coil body, a wire provided on the outer surface of the coil body forming a part of a first coil of the inductive element and a metallic separating plate that surrounds the outer surface of the coil body and forms a part of another coil of the inductive element.
- 16. An inductive element according to claim 15, characterised in that the core (11.1, 11.2) of the inductive element has a shape of two rectangular portions with a common edge (13), where the common edge is inserted into the hollow coil body and whereby the core preferably includes two E-shaped parts (11.1, 11.2).
- 17. An inductive element according to any of claims 15 to 16, characterised in that it includes at least two coil forms according to any of claims 1 to 13, where the core (11.1, 11.2) is inserted into the hollow coil body of each coil form.
- 18. Method for forming an inductive element with a hollow coil body (2), a core (11.1, 11.2) and at least two coils, characterised in that a coil area is provided by pushing at least two metallic separating plates (103) with an opening over the coil body and positioning the separating plates at a specific plate-distance by winding a wire in said coil area around an outer surface of the coil body thereby pressing the separating plates against a side support, where a part of a coil is provided by said wire and a winding of another coil is provided by a metallic separating plate (3).
- 19. Method according to claim 18, characterised in that said wire is fed from an outside of the coil body (102) to an inside of the coil body through a recess (127) on an inner surface of the coil body and from said recess to the outer surface of the coil body through an opening (126) in the coil body in a region of said recess.

5

Application-No. 2004/032158
Applicant: Delta Energy Systems (Switzerland) AG,



25

20. Method according to any one of claims 18 or 19, characterised in that a plurality of coil areas (124) provided by pushing a plurality of metallic separating plates over the coil body and spacing them equally at a specific plate-distance and in that a wire (128) is wound around the outer surface of the coil body in each coil area simultaneously.

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked.

belooks in the images metade out are not immited to the items encoded.				
☐ BLACK BORDERS				
☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES				
☐ FADED TEXT OR DRAWING				
☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING				
☐ SKEWED/SLANTED IMAGES				
☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS				
☐ GRAY SCALE DOCUMENTS				
LINES OR MARKS ON ORIGINAL DOCUMENT				
☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY				

IMAGES ARE BEST AVAILABLE COPY.

☐ OTHER:

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.